



HEAD OF MONITOR

ONEFLOW & FLOWMATIC

EN15-767 compliant monitor head

A high-quality protective broadcast jet

FlowMatic: automatic head

- The FlowMatic head has a regulating pressure of 6 bar.
- Flow ranges: - from 500l/min to 2000l/min for the FlowMatic 2000- from 1500l/min to 3000l/min for the FlowMatic 3000- from 1700l/min to 5000l/min for the FlowMatic 5000
- Pressure regulation helps maintain range.
- The wide diffused jet ensures a perfect protective screen.
- The polyurethane bumper is resistant to high temperatures, hydrocarbons and chemicals.
- Input 2"1/2 BSP.



OneFlow: Single-flow barrel head

- OneFlow heads are available in 1300, 2000 and 3000 l/min at 6 bar
- The diffused protective jet ensures a perfect protective screen.
- A robust and simple head: no bumper, no maintenance
- Input 2"1/2 BSP.



FLOWMATIC CHARACTERISTICS

	FlowMatic 2000	FlowMatic 3000	FlowMatic 5000
References	TFMA-200L-OIN	TFMA-300L-OIN	CDA-035-OI
Dimensions (cm)	H : 20 cm (Diffused) H : 23 cm (Jet stick) x Diam : 15 cm	H : 20 cm (Diffused) H : 23 cm (Jet stick) x Diam : 15 cm	H : 24 cm (Diffused) H : 29 cm (Jet stick) x Diam : 18.5 cm
Weight	3.6 kg	3.6 kg	6 kg
Flow	500 to 2000 lpm	1500 to 3000 lpm	1700 to 5000 lpm
Connections	2.5" BSP F	2.5" BSP F	2.5" BSP F
Guarantees	5 years	5 years	5 years

ONEFLOW CHARACTERISTICS

	OneFlow 1300	OneFlow 2000	OneFlow 3000
References	CDA-025-OI	CDA-023-OI	CDA-024-OI
Dimensions (cm)	H:15 cm (Diffused) H: 16.5 cm (Jet stick) x Diam:12 cm	H:15 cm (Diffused) H: 16.5 cm (Jet stick) x Diam:12 cm	H:17.5 cm (Diffused) H: 21.5 cm (Jet stick) x Diam:15 cm
Weight	1.8 kg	1.8 kg	3.2 kg
Flow	1300 lpm	2000 LPM	3000 LPM
Connections	2.5" BSP F	2.5" BSP F	2.5" BSP F
Guarantees	5 years	5 years	5 years



FlowMatic 2000 on Partner 2

Wide diffused jet ensures perfect screen protection

REDUCED COST OF OWNERSHIP

Very low maintenance due to the very robust design and materials used.

ZF.02.296.EN.4