



**NEO**  
**LEADER Fan**  
EASY POW'AIR  
TECHNOLOGY

## PETROL-DRIVEN FAN MT215 L

**Compact and lightweight:** 20.3 kg!

A very **concentrated and ultra-powerful** jet of air due to an optimal combination of:

- ▶ A high-strength propeller matched to the power of the engine
- ▶ A red double-layer monobloc shroud made of reinforced high-density polyethylene
- ▶ A high-tech composite grille

**Positioning from 0.90 m to 6 m** in front of a door without loss of power for:

- ▶ more space to move about
- ▶ less noise inside the building

With folding pull/steer handle for easier set-up

**Precise tilt adjustment**

from -10° to +20° with indicator for optimization of direction of air stream up entrance steps or down into a semi-basement

**Protective frame**

with w coating

**Stable & easy to handle** with large rear wheels

**Compact for easy storage in vehicle trunks**

### Characteristics

Model	MT215 L NEO
Reference	I60.10.062N
Open air flow	33 900 m <sup>3</sup> /h
PPV air flow according to AMCA	23 260 m <sup>3</sup> /h
Weight (dry)	20,3 kg
Dimensions L x H x D	530 x 495 x 555 mm
Propeller diameter	420 mm
Run time at full speed	1h40
Engine	HONDA GXH50 engine (4-stroke) 56% less CO than a 5 HP engine Assembly inspected and approved by Honda Motor Co., Ltd
Engine power	2.1 HP according to standard SAE J1349 of 2007
Noise level	84,5 dB at 3m
Ventilation type	PPV blowing
Application	Single door, e.g. house, small apartment block

### Optional accessories:

High expansion foam adapter without coupling delivered with 35m of polyane plastic film duct (products with coupling: see p. 52)	I60.20.105
Hour meter	I60.20.135
5m ventilation duct	I60.20.152

Ventilation tactics in the catalogue or at [www.leader-group.eu](http://www.leader-group.eu)  
Freely downloadable interactive ventilation courses at [www.leader-educexpert.com](http://www.leader-educexpert.com)  
As part of our policy of constant research to improve our products, we reserve the right to modify our products' characteristics at any time without notice

