



NEO
LEADER Fan
EASY POW'AIR
TECHNOLOGY

PETROL-DRIVEN FAN **MT225**

A very **concentrated and ultra-powerful** jet of air due to an optimal combination of:

- ▶ A high-strength propeller matched to the power of the engine
- ▶ A red double-layer monobloc shroud made of reinforced high-density polyethylene
- ▶ A high-tech composite grille

Positioning from 0.90 m to 6 m in front of a door without loss of power for:

- ▶ more space to move about
- ▶ less noise inside the building

Precise tilt adjustment

from -10° to +20° with indicator for optimization of direction of air stream up entrance steps or down into a semi-basement

Protective frame

with grey epoxy coating

Compact for easy storage in vehicle trunks

Characteristics

| Model | MT225 NEO |
|--------------------------------|---|
| Reference | I60.10.064N |
| Open air flow | 41 950 m ³ /h |
| PPV air flow according to AMCA | - |
| Weight (dry) | 28 kg |
| Dimensions L x H x D | 550 x 568 x 436 mm |
| Propeller diameter | 420 mm |
| Run time at full speed | 2h10 |
| Engine | HONDA GP 160 engine (4-stroke) Automatic engine cutout if oil runs out. Assembly inspected and approved by Honda Motor Co., Ltd |
| Engine power | 4.8 HP according to standard SAE J1349 of 2007 |
| Noise level | 93 dB at 3 m |
| Ventilation type | PPV blowing |
| Application | Single door, e.g. house, small apartment block |

Optional accessories:

| | |
|--|------------|
| Mister without coupling (products with coupling: see p. 52) | Consult us |
| High expansion foam adapter without coupling delivered with 35m of polyane plastic film duct (products with coupling: see p. 52) | I60.20.105 |
| 5m ventilation duct | I60.20.152 |

