



NEW !

PORTABLE MONITOR

PARTNER 2

Portable ground monitor EN15-767 certified

- Flow up to 3000 l/min
- High elevation up to 85° (from 25°)
- **Optional safety valve** in case of movement which reduces but doesn't stop the flow to keep enough flow for a good protection to the firefighter and reduces water hammer
- **Optional self-oscillating system** with adjustable angle between 20 and 40°
- Horizontal operation -20 to +20°
- Compact size in folded position
- Equipped with a **protected pressure gauge**
- 5 flexible **stainless-steel legs**
- Body in **hard coat anodized aluminum**
- **Full time swivel inlet** 2.5" BSP F or 4" BSP M



Protected pressure gauge and optional safety valve

As part of our policy of constant research to improve our products, we reserve the right to modify our products' characteristics at any time without notice

Characteristics

Model (without nozzle)	Weight	Dimensions Length x width x height	Item numbers	Inlet
Partner 2 with Safety valve	10.2 kg	Folded: 51 x 24 x 32	CPA-022-OP	2.5" BSP F
		Unfolded: 64 x 65 x 32	CPA-022-8P	4" BSP M
Oscillating Partner 2 with Safety valves	13.8 kg	Folded: 76 x 36 x 36	CPA-122-OP	2.5" BSP F
		Unfolded: 71 x 65 x 36	CPA-122-8P	4" BSP M



*Safety valve



**Oscillating device (optional)

Options

Tips:

- **OneFlow:** fixed flow monitor nozzle
Ref: CDA-023-OI: 2000 l/min @ 6 bar
Ref: CDA-024-OI: 3000 l/min @ 6 bar
- **FlowMatic:** automatic monitor nozzle
Ref: CDA-020-OI: 2000 l/min @ 6 bar
Ref: CDA-021-OI: 3000 l/min @ 6 bar



Accessories:

- **Storage bracket in stainless steel** Ref: CDA-200-II
Weight: 3.1kg / 6.9 lbs Dim: 5 x 25 x 49 cm / 2" x 9.9" x 19.3"
- **Inlet couplings on request:**
BS336, Storz, DSP, Barcelona...
- **Inlet Siamese: 2 x 2.5" BSP:** for Partner in 4" BSP
Ref: I18.20.035



Reduced cost of ownership:

Very light maintenance requirement due to the nozzle design and materials used.



ZF.02.292.EN.3