



**NEW !**

## PORTABLE MONITOR

# PARTNER 2

## Portable ground monitor EN15-767 certified

- Flow up to 3000 l/min
- High elevation up to 85° (from 25°)
- **Optional safety valve** in case of movement which reduces but doesn't stop the flow to keep enough flow for a good protection to the firefighter and reduces water hammer
- **Optional self-oscillating system** with adjustable angle between 20 and 40°
- Horizontal operation -20 to +20°
- Compact size in folded position
- Equipped with a **protected pressure gauge**
- 5 flexible **stainless-steel legs**
- Body in **hard coat anodized aluminum**
- **Full time swivel inlet** 2.5" BSP F, 2.5" NH F or 4" BSP M



Protected pressure gauge and optional safety valve

As part of our policy of constant research to improve our products, we reserve the right to modify our products' characteristics at any time without notice

## Characteristics

Model (without nozzle)	Weight	Dimensions Length x width x height	Item numbers	Inlet	Outlet
Partner 2 with Safety valve	10.8 kg	Folded: 51 x 24 x 32 Unfolded: 64 x 65 x 32	CPPA-022-OP	2.5" BSP F	2.5" BSP M
			CPPA-022-S5	2.5" NH F	2.5" NH M
			CPPA-022-8P	4" BSP M	2.5" BSP M
Oscillating Partner 2 with Safety valves	14.0 kg	Folded: 76 x 36 x 36 Unfolded: 71 x 65 x 36	CPPA-122-OP	2.5" BSP F	2.5" BSP M
			CPPA-122-S5	2.5" NH F	2.5" NH M
			CPPA-122-8P	4" BSP M	2.5" BSP M



\*Safety valve



\*\*Oscillating device (optional)

## Options

- **OneFlow:** fixed flow monitor nozzle  
Ref: CDA-025-OI: 1300 l/min @ 6 bar  
Ref: CDA-023-OI: 2000 l/min @ 6 bar  
Ref: CDA-024-OI: 3000 l/min @ 6 bar
- **MultiFlow:** Selectable flow nozzle  
Réf.: CDA-040-OI: 500 à 3000 l/min @ 6 bar
- **FlowMatic:** automatic monitor nozzle  
Ref: TFMA-200L-OIN: 2000 l/min @ 6 bar  
Ref: TFMA-300L-OIN: 3000 l/min @ 6 bar
- **Foam barrel:** Foam tube 2000 or 3000 l/min  
Extra short (450mm) low expansion that can either be screwed directly onto the monitor outlet or mounted via Storz coupling
- **Storage bracket in stainless steel** Ref: CPDA-200-II  
Weight: 3.1kg / 6.9 lbs Dim: 5 x 25 x 49 cm / 2" x 9.9" x 19.3"
- **Inlet couplings on request:**  
BS336, Storz, DSP, Barcelona...
- **Inlet Siamese: 2 x 2.5" BSP:** for Partner in 4" BSP  
Ref: I18.20.036



## Reduced cost of ownership:

Very light maintenance requirement due to the nozzle design and materials used.  
Warranty: 5 years

ZF.02.292.EN.4