



## OPTIONAL WIRELESS REMOTE CONTROL

MORE FLEXIBILITY DURING FIRE TRAINING USING A LEADER FLAME GENERATOR!

TRIGGERING THE FLAMES BY GETTING RID OF CABLE MANAGEMENT:

- GF42  
=> OPTION PLUGS INTO THE SOLENOID VALVE MODULE
- AEROS 2  
=> OPTION PLUGS DIRECTLY INTO THE PAN



GF42 and its solenoid valve module using the wireless remote control option



Aeros 2 using the wireless remote control option

### PRACTICE

Space-saving, lightweight and robust, the "wireless remote-control option" accessory consists of a wireless remote control and a magnetic transmitter/receiver antenna box that attaches easily to any gas cylinder.

### WIRED OR WIRELESS CONTROL

To operate the whole, simply connect the antenna box to the cable of the wired remote control of the Aeros 2 or the solenoid valve module of the GF42 which now automatically integrate a connector to allow the connection. The trainer can reconnect his wired remote control in the same way.



# BENEFITS

---

The set allows the trainer to accompany his trainees as close as possible to the fire with more flexibility:

- Removal of the wired remote control cable management
- Wireless range of 30m (100 ft)
- Quick and easy implementation
- Reduced maintenance
- Economical: the accessory remains a non-mandatory option
- Flexibility: the accessory can be purchased later with the purchase of the unit to be equipped (for Aeros 2 and solenoid valve modules purchased from Dec. 2021)
- Wired alternative with the standard remote control in case of interference

# TECHNICAL CHARACTERISTICS

---

|                     |   |
|---------------------|---|
| Reference           | V90. 80.083   |
| What's included     | <ul style="list-style-type: none"><li>• Magnetic transmitter / receiver box with male connector</li><li>• Wireless remote control and its neck strap</li><li>• Instructions for use</li></ul>         |
| Size (with antenna) | H 275 x W 185 x D 85 mm (H 10.8 x W 7.3 x D 3.4 in)   |
| Weight              | 1000g (2.2 lbs)   |
| IP                  | <ul style="list-style-type: none"><li>• Magnetic transmitter / receiver antenna box: IP65</li><li>• Male slot of the antenna box: IP65 (plugged in)</li><li>• Wireless remote control: IP65</li></ul> |
| Range               | 30m in open field (100 ft)  |
| Frequency           | 433 MHz usable in the European Union (other countries: check the country's legislation)   |
| Power supply        | <ul style="list-style-type: none"><li>• Antenna box: Powered by the battery of the device to which it is connected</li><li>• Wireless Remote Control: GP27A / 12V / 18mAh Battery</li></ul>           |
| Temperature of use  | -20°C to +50°C (-4°F to +122°F)   |
| Warranty            | 1 year  |